# THREE ELEPHANT® Dense Soda Ash Sodium Carbonate Safety Data Sheet

# 1. Product and Company Identification

Product Name	THREE ELEPHANT® Dense Soda Ash	
Other Product Name(s)	Soda Ash, Sodium Carbonate; Washing Soda	
Product Use	Ceramics, chemical reagents, detergents, soaps, glass containers, auto glass, flat glass, electroplating, metal cleaning, paper coating, water softening, enameling, and other general chemical uses.	
Manufacturer	SEARLES VALLEY MINERALS INC. 13200 MAIN STREET; P.O. BOX 367 TRONA, CALIFORNIA 93592-0367 Information (760) 372-2291	
Emergency Telephone Numbers	1-800-424-9300 (USA/Canada CHEMTREC) +1 (703) 527-3887 (International & Maritime CHEMTREC)	

### 2. Hazards Identification

**Emergency Overview**: A white crystalline granular solid that can irritate skin, eyes and respiratory tract. Not flammable.

OSHA Regulatory Status	Hazardous	
WHMIS Regulatory Status	Hazardous	
OSHA Classification	Eye corrosion/irritation 2A	
OSHA Signal Word	WARNING	
OSHA Hazard Statements	Causes serious eye irritation.	
OSHA Precautionary	Wear protective gloves and safety eyewear. Wash thoroughly after	
Statements	handling.	
	If on skin, wash with plenty of water. Wash contaminated clothing before	
	reuse. If in eyes: Rinse cautiously with water for several minutes.	
	Remove contact lenses, if present and easy to do. Continue rinsing.	
	If inhaled: Remove person to fresh air and keep comfortable for	
	breathing.	
	If skin irritation occurs or eye irritation persists, get medical attention.	
	Store in a well ventilated place. Keep container tightly closed.	
	Dispose of container in accordance with Federal and local regulations.	
OSHA Label Symbols	<u>(!</u> )	
Other Hazards Not	None	
Specified by OSHA		
44 KI (	at OCHA 9 FHCA label as a visa as a set and as a visa at a delitional absence	

<sup>\*\*</sup> Note: Label designed to meet OSHA & FHSA label requirements and may contain additional phrases.

#### **Potential Health Effects:**

i otolitiai i loaitii E	
Skin	Can cause mild skin irritation.
Eyes	Causes eye irritation.
Ingestions	Low toxicity. May cause discomfort. In rare cases may cause irritation or burns
	to digestive tract.
Inhalation	May cause irritation if inhaled.
Chronic Effects	None.

Ingredients found on established carcinogen lists:

Ingredient	NTP Status	IARC Statue	OSHA List
No ingredients listed in this section.			

# 3. Composition / Information on Ingredients

Chemical Name	CAS#	EINECS #	Wt. %
Sodium carbonate*	497-19-8	207-838-8	99 – 100

<sup>\*</sup>May contain trace amounts of naturally-occurring substances including arsenic and other metals. See Section 15 for California Proposition 65 Warning.

### 4. First Aid Measures

Skin	Wash with plenty of water. Wash contaminated clothing before reuse. Seek medical attention if skin irritation occurs.
Eyes	Rinse eyes cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention if irritation persists.
Ingestions	If you feel unwell, contact a doctor or poison control center.
Inhalation	Remove to fresh air.
Advice to Physician	Treat symptomatically.

# 5. Fire Fighting Measures

Extinguishing Media:	Any media suitable for surrounding fire.	
Fire/Explosion Hazards:	None indicated.	
Fire Fighting Procedures:	Wear normal firefighting gear suitable for surrounding fire. Self-contained respiratory protection may be required.	
Flammable Limits:	None.	
Flash Point	Not flammable.	
Autoignition Temperature:	None.	
Hazardous Combustion Products:	Produces carbon dioxide if heated above 1832 °F (1000 °C).	

### 6. Accidental Release Measures

Personal	Wear proper personal protective equipment indicated in Section 8.
Precautions:	
Containment:	Not normally required as this is a solid material not normally mobile.
Clean Up:	Sweep up and place into container for reuse and/or disposal.
Notification	None normally required.
Requirements:	

# 7. Handling and Storage

Handling:	Wear proper personal protective equipment indicated in Section 8. Wash hands before eating or drinking.
Storage:	Should be stored in a dry location. Keep packages tightly closed to minimize dust formation. Keep out of the reach of children.

# 8. Exposure Controls / Personal Protection

Engineering	Use local exhaust to keep airborne level below safe exposure guidelines listed
Controls:	below.

### **Personal Protective Equipment:**

Eyes and Face:	Wear safety glasses or chemical dust goggles to avoid accidental eye contact.	
Respiratory:	Not required for properly ventilated areas. Otherwise use a NIOSH approved dust	

	respirator.
Hands, Arms,	Not normally required. Use work gloves when handling product transfers or if skin
and Body:	is already irritated. Use rubber or neoprene gloves for handling product solutions.
Other	Safety shower and an eyewash should be available for emergency exposures.

### **Exposure Guidelines:**

•						
Ingredient	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL	California PEL	
Sodium carbonate Handle as particulates	3 mg/m <sup>3</sup> respirable dust	None	15 mg/m <sup>3</sup> total dust	None	10 mg/m <sup>3</sup> total dust	
not otherwise regulated	10 mg/m <sup>3</sup> inhalable dust		5 mg/m <sup>3</sup> respirable dust		5 mg/m <sup>3</sup> respirable dust	

# 9. Physical and Chemical Properties

Appearance & Physical State	White, crystalline, granular solid
Odor:	None
Odor Threshold:	None
pH (1% solution)	11.4 (1% solution at 68 °F)
Specific Gravity:	2.533
Bulk Density	55 – 65 lbs/ft <sup>3</sup>
Initial Boiling Point & Range:	Not applicable
Melting Point /Freezing Point:	1563 °F (851 °C)
Evaporation Rate:	Not applicable
Percent Volatile:	None
Solubility in Water	16.3% at 73 °F (22.8 °C)
Vapor Density:	Not determined
Vapor Pressure:	Not determined
Upper/ Lower Flammable Limits:	None
Flash Point	None
Auto ignition Temperature:	Not flammable
Flammability (solid, gas)	Not flammable
Octanol/water partition coefficient	Not determined
Decomposition temperature	Not determined
Viscosity	Solid – Not applicable

# 10. Stability and Reactivity

Stability:	Normally stable.	
Conditions to Avoid:	Keep Soda Ash away from aluminum powder, sulfuric acid, fluorine, phosphorous pentoxide, ammoniacal silver nitrate, and molten lithium.	
Materials to avoid	May react with strong acids. May form caustic soda in the presence of hydrated lime and moisture.	
Polymerization:	Will not occur.	
Hazardous Decomposition Products	Soda Ash decomposes at temperatures above 1000 °C, releasing carbon dioxide gas (CO2). Carbon dioxide is an asphyxiant and may affect respiration rate or interfere with breathing. The sodium oxide residue sublimes at 1275 °C, forming vapors and mists of caustic soda on contact with moisture or water.	

# 11. Toxicological Information

Eye:	Causes serious eye irritation.	
Skin:	LD <sub>50</sub> (dermal, rabbit) > 2000 mg/kg. Can cause mild irritation.	

Oral:	LD <sub>50</sub> (oral, rat) – 2800 mg/kg	
Inhalation:	The LC <sub>50</sub> for inhalation are 800, 1200 and 2300 mg/m <sup>3</sup> for guinea pig, mice and rat respectively.	
Chronic:	c: Not considered carcinogenic or a reproductive hazard.	

# 12. Ecological Information

Acute ecotoxicity:	Fishes, Lepomis macrochirus, LC <sub>50</sub> , 96 h, 300 mg/l	
	Crustaceans, Ceriodaphnia dubia, EC <sub>50</sub> , 48 h, 200 - 227 mg/l	
Chronic ecotoxicity: Not determined.		
Other Information Not considered to bioaccumulate or to be persistent in the environment.		

# 13. Disposal Considerations

RCRA Status	Not a hazardous waste if discarded.	
Disposal Method:	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult all federal, state, and local hazardous waste regulations to ensure complete and	
	accurate classification and disposal.	

## 14. Transportation Considerations

DOT Proper Shipping Name:	Not regulated for transport
DOT Primary Hazard Class	Not applicable
DOT UN / NA Number:	Not applicable
DOT Packing Group	Not applicable
TDG (Canada)	Not regulated
IMDG (International water)	Not regulated
ICAO (Air transport)	Not regulated

# 15. Regulatory Information

### **UNITED STATES:**

Toxic Substances Control Act (TSCA)

TSCA Inventory Status:	Listed on TSCA Chemical Inventory.	
Other TSCA Issues:	None	
NSF/ANSI 60	Maximum Use Level (MUL) for potable water is 100 mg/l.	NSF.  Certified to NSF/ANSI 60

### **SARA Title III/CERCLA**

Ingredients with "Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs).

Ingredient		SARA/CERCLA RQ (lb)	SARA EHS TPQ (lb)
No ingredients listed in	this section.		

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SARA 311 Hazard Class: Immediate

### **SARA 313 Toxic Chemicals**:

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percent are found in Section 2.

Ingredient	Comment

No ingredients listed in this section. ---

### State Right-To-Know

### **California Proposition 65**

**WARNING:** This product can expose you to chemicals including arsenic, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

Additional Regulatory Information:	Not listed in Clean Water Act or in Safe Drinking Water Act.
raditional Rogalatory Illioniation.	1 Not noted in Cican Water Not of in Care Difficing Water Not.

#### CANADA:

WHMIS Classification:	D2B	
WHMIS Ingredient Disclosure List	Sodium carbonate is listed.	
DSL Status (Domestic substances Listed on DSL.		
list)		

Ingredients for this product also found on the chemical inventories of Australia, China, Korea, European Union, Japan and the Philippines.

### 16. Other Information

- Unless otherwise indicated, this materials is not intended for human consumption and is for industrial
  use only.
- · Keep out of the reach of children.

Issue Date:	August 21, 2018	
Previous Issue Date:	March 15, 2018	
Changes from previous version: Updated Se		s 3 and 15. California Proposition 65 Information.

#### National Fire Protection Assoc. (NFPA) Classification:

4 = Severe; 3 = Serious; 2 = Moderate; 1 = Slight, 0 = Minimal Health 2

Flammability 0 Reactivity 0

### **Hazardous Materials Information Systems (HMIS):**

4 = Extreme; 3 = High; 2 = Moderate; 1 = Slight; 0 = Insignificant

Health 2 Flammability 0 Physical Hazard 0

The information appearing herein is based upon data obtained from the generator and/or recognized technical sources. While the information is believed to be accurate, Searles Valley Minerals Inc. (SVM) makes no representations as to its accuracy or sufficiency. Conditions of use are beyond SVM's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the material is suitable for their particular purposes and they assume all risk of their use, or reliance upon, information contained herein. This information relates only to the material designated herein and does not relate to its use in combination with any other material or in any other process.